



INVESTOR IN PEOPLE

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed

*Evans*


Dated

5 February 2001

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

An Executive Agency of the Department of Trade and Industry

**THIS PAGE BLANK (USPTO)**



# Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

## 1. Your reference

X. CHEN 20

## 2. Patent application number

(The Patent Office will fill in this part)

21 AUG 2000

0020579.9

## 3. Full name, address and postcode of the or of each applicant (underline all surnames)

Lucent Technologies Inc.  
600 Mountain Avenue,  
Murray Hill,  
New Jersey 07974-0636,  
United States of America

Patents ADP number (if you know it)

07039555001

If the applicant is a corporate body, give the country/state of its incorporation

Delaware/U.S.A.

## 4. Title of the invention

SUPPORTING IP ON ABIS INTERFACE

## 5. Name of your agent (if you have one)

C.S.T. BUCKLEY

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Lucent Technologies (UK) Ltd.  
5 Mornington Road,  
Woodford Green,  
Essex IG8 0TU,  
England

Patents ADP number (if you know it)

00003939003

## 6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country	Priority application number (if you know it)	Date of filing (day / month / year)
GB	0010059.4	25.4.2000

## 7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application	Date of filing (day / month / year)

## 8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
  - b) there is an inventor who is not named as an applicant, or
  - c) any named applicant is a corporate body.
- See note (d))

# Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document


Continuation sheets of this form

Description 7

Claim(s) 2

Abstract 1

Drawing(s) 2



10. If you are also filing any of the following, state how many against each item.

Priority documents 1

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77) 1

Request for preliminary examination and search (Patents Form 9/77) 1

Request for substantive examination (Patents Form 10/77) 1

Any other documents (please specify)

11. I/We request the grant of a patent on the basis of this application.

Signature

Date

*C.S.T. BUCKLEY*

14.8.2000

12. Name and daytime telephone number of person to contact in the United Kingdom

C.S.T. BUCKLEY

0208 504 2824


## Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication, or if such communication has been given, or any such direction has been revoked.

## Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

Statement of inventorship and of  
right to grant of a patent



The Patent Office

Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference

X. CHEN 20

2. Patent application number  
(if you know it)

21 AUG 2000

0020579.9

3. Full name of the or of each applicant

LUCENT TECHNOLOGIES INC

4. Title of the invention

SUPPORTING IP ON ABIS INTERFACE

5. State how the applicant(s) derived the right  
from the inventor(s) to be granted a patent

as employers

6. How many, if any, additional Patents Forms  
7/77 are attached to this form?  
(see note (c))

7. I/We believe that the person(s) named over the page (and on  
any extra copies of this form) is/are the inventor(s) of the invention  
which the above patent application relates to.

Signature

Date

*C.S.T. Buckley*

14.8.2000

8. Name and daytime telephone number of  
person to contact in the United Kingdom -

C.S.T. BUCKLEY

0208 504 2824

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there are more than three inventors, please write the names and addresses of the other inventors on the back of another Patents Form 7/77 and attach it to this form.
- When an application does not declare any priority, or declares priority from an earlier UK application, you must provide enough copies of this form so that the Patent Office can send one to each inventor who is not an applicant.
- Once you have filled in the form you must remember to sign and date it.

Enter the full names, addresses and postcodes of the inventors in the boxes and underline the surnames

XIAOBAO X CHEN,  
17 Beech Drive,  
Swindon,  
Wiltshire SN5 5DQ,  
United Kingdom

Patents ADP number (if you know it):

0496544 5001

Patents ADP number (if you know it):

Patents ADP number (if you know it):

**Reminder**

Have you signed the form?

# SUPPORTING IP ON ABIS INTERFACE

5

This invention relates to mobile telecommunications networks, such as the GSM (Global System for Mobile telecommunications) and especially to EDGE (Enhanced Data rates for GSM Evolution).

Conventional telephone networks are circuit switched, and naturally the early  
10 mobile telecommunications networks were also circuit switched. Later generations, such as the GPRS (General Packet Radio Service) are packet switched, and the use of the packet switched Internet Protocol (IP) is now increasing very rapidly.

The second generation GSM is illustrated in Figure 1. The GSM 10 comprises a Radio Access Network (RAN) 12 and a Core Network (CN) 14. Within the RAN are  
15 a number of Base Station Controllers (BSCs) 16 each controlling a number of Base Transceiver Stations (BTSs) 18. The BSCs 16 and BTSs 18 communicate over the interface Abis, which is circuit switched. A mobile terminal 20 is associated with a BTS 18. Within the CN 14 are a number of Mobile Switching Centres (MSCs) 22. The CN 14 and the RAN 12 are both circuit switched.

20 With the rapid development of the use of IP, it is highly desirable to operate current equipment using IP; it is an object of the invention to provide an arrangement so that packet switched operation is possible over the Abis interface.

According to the invention the mobile telecommunications system comprising at least one primary network unit capable of supporting a plurality of secondary  
25 network units, each secondary network unit being capable of supporting a plurality of mobile users, the primary and secondary network units communicating across a circuit switched interface, characterized by means to provide an Internet Protocol tunnel between a primary network unit and a secondary network unit which it supports.

The network may be an EDGE network when the primary network unit is a  
30 BSC and the secondary network units are each a BTS.

In the accompanying drawings, Figure 1 illustrates the prior art. The invention will be described by way of example only with reference to figures 2, 3 and 4 in which:-

Figure 2 illustrates IP tunneling over an Abis interface;

Figure 3 illustrates a typical packet construction; and

35

Figure 4 illustrates an IP tunnel.

Figure 2 illustrates the protocol stacks that deploy IP as the access/transport bearer for layer 3/2 message exchanges between a BSC 16 and a BTS 18. Within the BSC 16 there are several Packet Control Units (PCUs) 30 (two of which are illustrated) carrying three protocol layers; these are a Data Link (DL)/ Physical Layer (PHY) 32; an IP layer 34; and a GPRS layer 3/layer 2 (data traffic and signaling) message layer 36. Within BTS 18 there are two more Channel Codec Units (CCUs) such as 40, each having a Data Link layer (DL) /Physical Layer (PHY) 42, an IP layer 44, and a GPRS L3/L2 message layer 46. There is also an Abis interface 52 (a circuit switched interface) between the BSC 16 and the BTS 18.

In the inventive arrangement, an IP tunnel, such as tunnel 50, is set up between the IP layer 34 in BSC 16 and the IP layer 44 in BTS 18. When GPRS layer 2 messages are to be exchanged between layer 36 of the PCU 30 and layer 46 of the CCU 40, the messages can pass through the IP tunnel 50 and across the Abis interface 52; the messages or other data are carried in IP packets.

The IP tunnel is bi-directional, and the BSC 16 controls the set-up, the maintenance and the close or release of the tunnel. IP is used as the access as well as the transport bearer to tunnel the layer 2 and layer 3 messages.

Supporting the IP on the Abis interface in this way includes two aspects.

- a) Using IP as the accessing mechanism/protocol
- b) Using IP as the network routing mechanism/protocol.

While the invention will be exemplified based on the assumption of using IP as the accessing mechanism/protocol, underneath network links or routing/switching mechanisms may well be non-IP, such as ATM.

When IP is used as an accessing or addressing protocol, it is used to identify the traffic source, and the destination and the user data traffic/information is carried in the payload of IP packets that will then be routed to the required destination as indicated by the destination address. The routing protocol may be IP or non-IP such as ATM.

In the example in Figure 2, the DL layer/Physical Layer 32, 42 may operate by ATM.

A typical packet construction is shown in Figure 3. The packet 60 has a header



H 62 and a payload P which comprises an Abis-Message Type Field A 64 and a message M 66.

5 The AbisMMMessage Type Field 64 is eight bits long and can therefore be any one of two hundred and fifty six messages; this field is used to identify the messages in the payload 66; the messages may be L3/L2 messages which may be multiplexed over the same IP tunnel between a pair of BTS and BSC, when the Abis field is used to demultiplex the messages. Such use of an extra field can be regarded as a proprietary extension to the IETF (Internet Engineering Task Force) standard protocol.

10 Considering now the use of IP as a network routing mechanism; IP is used as a routing protocol to route IP packets across the network (between hosts/network nodes) across the network link. In this scenario, IP is used as the network layer routing protocol that is responsible for delivering the IP packets across the network to the destination. This scenario also explicitly excludes the use of ATM as the routing/switching mechanism.

15 In such a network, the BSC 16 and BTS 18 may form intermediate nodes in the route. The intermediate nodes, BTS and the BSC, will read the packet headers and send the packet to the correct destination. The packets are routed to the BSC 16 or the BTS 18 (depending on the direction, to or from the mobile 20) by providing the address of the BSC or the BTS as the destination address of the packet. The packet header and  
20 payload are transferred between the BSC and BTS through the IP tunnel 50 as before, and continue on their path.

It is important for the messages between the BSC 16 and the BTS 18 always to travel through the same tunnel 50. This can be achieved by using as the source and the destination address for packets, the explicit IP addresses of the BTS and BSC in the  
25 packet headers, and then transposing them to ensure that a return IP packet carrying the response Layer 2/Layer 3 messages travels by the same route.

In one arrangement, all layer2/layer3 messages for all CCUs in a BTS share the same IP tunnel with its corresponding BSC; the Abis Message Type Field is divided into two sub-fields, one to indicate the GPRS layer2/layer3 messages and the other  
30 indicating the CCU. In another arrangement, an IP tunnel is set up and used exclusively between the PCU and one CCU. No demultiplexing between the messages from

different CCU is required.

With the arrangement described, the signaling and data messages are multiplexed over the same IP tunnel, i.e. tunnel 50, that provides "point-to-point" connectivity between the BTS 18 and the BSC 16. At the receiving side either the BTS  
5 (for the downlink) or the BSC (for the uplink) demultiplexes the tunneled Abis messages by indexing the Abis message type field.

Different processing and handling priorities can be achieved by filtering the corresponding fields in the IP header 62.

The selection and allocation of appropriate code and channels is based on  
10 packet handling priority information contained in the IP header 62 and the Abis Message Type Field 64.

The successful set up of a RR (Radio Resource ) session will activate an active "IP tunnel" associated with a specific set of codes and channels that have been allocated by the BSC . The necessary status record is set up corresponding to the IP tunnel.

15 De-allocation of a channel will de-activate an existing active IP tunnel and the associated status recorded will be deleted.

As a mobile 20 wanders so that radio resource handover is necessary, no handover recognition or decision is made by BTS 18. Once a handover decision is made, the BSC 16 issues an IP tunnel set-up command to the new BTS (for intra-BSC  
20 handover) and subsequently passes all the information related to the mobile 20 to the new BTS. After setting up a new IP tunnel to the new BTS, the BSC 16 issues an IP tunnel close command to close the old IP tunnel to BTS 18 associated with the mobile 20 which has just performed the handover.

The radio channel management and the terrestrial channel management are  
25 controlled by the BSC 16. No changes are required to existing control procedures.

The message sequences across the Abis interface are not affected by the IP tunneling. The additional messages and the message exchange sequences are related to the set-up, maintenance and the release of the IP tunnel as well as the multiplexing/de-multiplexing operations of L3/L2 messages over the IP tunnel. Efforts are made to  
30 maintain a maximum openness of the message handling mechanisms between the L3/L2 functional layers and the IP tunnel layer so that further evolved mechanisms can be

deployed.

Due to the simple fact that the IP tunnels provide a transparent bearer between the BTS and the BSC, and that no changes are incurred over the specifications of existing interfaces except that an IP tunnel layer is added with a minimum set of control  
5 messages and control procedures, the existing O&M (Operational & Maintenance support over current standardized interfaces is barely affected.

The existing packet prioritization and differentiation, as well as pre-emption mechanisms that have been or are being defined by IETF (Internet Engineering Task Force), can be leveraged to the greatest extent to achieve a flexible and effective IP  
10 packet priority and pre-emption. For example, explicit IP packet priority levels can be attached within the IP header and the associated pre-emption information is stored at the BTS and the BSC with the IP tunnel state records corresponding to each active IP tunnel. Another example is the DS (Differentiated Service) fields as defined in DiffServ can be exploited to achieve the appropriate packet priority and pre-emption combined  
15 with managed queuing.

With the use of IP tunnels for traffic transport between the BTS and BSC, existing IETF defined mechanisms such as DiffServ can be easily introduced for packet classification and for Quality of Service (QoS) and CoS (Class of Service) differentiation.

20 A simple model of an IP tunnel 50, connecting the BSC 16 and the BTS 18 is illustrated in Figure 4; the BSC and BTS each contain a Packet Classifier and Marker (PCM) and Traffic Conditioner (TC) 56, 58 respectively, attached at the respective ends of the tunnel 50. Each tunnel end point has an ID, tunnel ID (BSC) and tunnel ID (BTS) respectively; these IDs are used, in addition to the IP addresses of the BSC and  
25 BTS, in packet headers to ensure that packets are routed through the tunnel.

Each PCM/TC looks at the Abis Message Type Field in each packet, classifies the packet, and then places a packet differentiation marking in the IP header of each packet. The PCM classifies the tunneled Abis messages according to predefined rules.

The marking applied by each PCM/TC 56, 58 can be in DSCP format  
30 (Differentiated Service Code Point).

For each tunneling packet, its DSCP is checked and then used to decide a

corresponding forwarding priority and the expected traffic transmission characteristics to be achieved by the selected forwarding behavior. A packet that exceeds the prenegotiated QoS will be re-marked by the PCM to be either the Best-Effort class or simply discarded by the TC.

5        Thus standard QoS mechanisms and real time traffic management mechanisms such as DiffServ, can be supported, in particular

- i)        traffic classification
- ii)       congestion management
- iii)      congestion avoidance
- 10       iv)       queuing
- v)       backhaul diversity

Congestion management is achieved by proper traffic conditioning through a TC 56, 58 via the means such as traffic shaping and policing.

15       Congestion avoidance is achieved by using the TC (shaping/policing) in combination with a three way handshake Request-Reply-Ack) mechanisms that provides instant traffic processing and load information at each end of the IP tunnel.

Dynamic and flexible management of the IP tunnels can also facilitate congestion control.

20       Separate queues are set up and configured and appropriate scheduling (CBQ, ⊗ Class Based Queueing), WFQ (Weighted Fair Queueing), RED (Random Earliest Detection) are deployed in combination with the PCM/TC/DSCP to guarantee efficient and effective traffic separation (separating signaling from the user data) and the QoS/CoS differentiation.

25       Efforts can be made to guarantee maximum compatibility with the existing circuit switched interface Abis. Due to the nature of the transparent transport through the IP tunnels, the BTS (CCUs) and the BSC (PCUs) serve as the termination points for the IP tunnels where the Abis messages are extracted from the tunneling IP packet and send to the circuit-switched Abis interface. No message change or protocol  
30       conversion is required.

The invention has been described with reference to Figure 2 illustrating a BTS

18 and a BCS 16 in the GPRS/EDGE system with an IP tunnel between them. The invention is equally applicable to a PCU Packet Control Unit or its equivalent in a Radio Network Controller (RNC) and a CCU Channel Codec Unit or its equivalent in a Node B in the UMTS (Universal Mobile Telephone System). An IP tunnel can be set  
5 up to transfer packets in the same way. Thus upgrading of UMTS to EDGE is made easier because handover control is facilitated. This is largely because the connectivity which is frequently switched on and off during the handover is achieved and maintained by the simple stateless IP accessing and routing mechanism that is independent of the underlying link layer control and transport mechanisms. As a result, it can dramatically  
10 reduce the processing overhead and the connection set-up delays as would be incurred by the connection-oriented mechanism. Furthermore, handover efficiency and reliability is expected to be improved by means of IP tunneling due to the dynamic routing capability of IP packets through the tunnels.

When the intermediate network link is ATM-based or is otherwise non-IP, then  
15 there will be no IP at the source or the destination to read the packet address. It is now necessary to use IP over ATM or IP switching or MPLS (Multi-Protocol Label Switching) in order to transport an IP packet through the network link. The description above about supporting IP based Abis applies to both RFC 791 standard (V4) and RFC 791 standard (V6).

20 While Figure 2 depicts the option of locating a PCU 30 in the BSC 16, the PCU maybe located at any other convenient position in the network.

As an alternative to using IP tunneling, TCP/IP (Transport Control Protocol IP) or UDP/IP (User Data Protocol IP) can be used for both information exchanges over the traffic channels and the signaling channels. With use of these protocols, it is not  
25 necessary to use any proprietary extension (equivalent to the inclusion of the Abis Message Type Field).

## CLAIMS

1        A mobile communications system comprising at least one primary network unit (16) capable of supporting a plurality of secondary network units (18) each capable of supporting a plurality of mobile users (20), the primary and secondary  
5 network units communicating across a circuit switched interface (52), characterized by means (16) to provide an Internet Protocol tunnel (50) between a primary network unit and a secondary network unit which it supports.

2        A system according to Claim 1 in which the primary network unit is a Base Station Controller (16) and the secondary network unit is a Base Transceiver  
10 Station (18).

3        A system according to Claim 1 in which the primary network unit is a Radio Network Controller and the secondary network unit is a Node B.

4        A system according to Claim 2 in which the Internet Protocol tunnel is arranged between a Channel Codec Unit (40) in a Base Transceiver Station (18) and a  
15 Packet Control Unit (30) in a Base Station Controller (16), the Channel Codec Unit (40) and the Packet Control Unit (30) each comprising a Data link Layer/Physical Layer (32, 42) an Internet Protocol layer (34, 44) and a GPRS layer 3/layer 2 message layer (36, 46).

5        A system according to any preceding Claim in which each end of the Internet Protocol tunnel (50) is associated with a Packet Classifier and Marker (56, 58)  
20 in respectively each primary network unit (16) and each secondary network unit (18).

6        A system according to any preceding Claim in which the circuit switched interface is an Abis interface (52).

7        A system according to Claim 6 in which each packet passing between a primary and a secondary network unit (16, 18) is arranged to contain adjacent the  
25 packet header an Abis-message type field (64) which identifies the type of messages.

8        A system according to Claim 7 in which the Abis-type message field identifies the secondary network elements (40) in the BTS .

9        A system according to Claim 7 or Claim 8 in which the messages and  
30 the payload are multiplexed GPRS layer 3/layer 2 messages and the Abis-Message Type Field (64) is used to de-multiplex the messages on arrival of a packet at its destination.

10 A system according to any one of Claims 1 to 5 in which the circuit switched interface is an interface between a RNC and a Node B in a third generation mobile telecommunications network.

## ABSTRACT

### SUPPORTING IP ON ABIS INTERFACE

5            In an EDGE system, an IP tunnel is provided between a BSC (16) and each  
BTS (18) which it supports; packets can then be tunneled across the circuit-switched  
Abis interface between the BSC and the BTS.

10           Figure 2






FIG. 1




FIG. 2




FIG. 3

***This Page Blank (uspto)***




FIG-4

***This Page Blank (uspto)***